

COSMO

Live a vibrant life, a beautiful life, a passionate life

- Similar lighting performance as a traditional fluorescent but using significantly less energy.
- Easy installation and maintenance
- Environmentally friendly and maintenance free.
- Choice of Round and square trim



INDOOR LIGHTING

RECESS DOWN LIGHT



COLOR TEMPERATURE

3000K 4000K 6500K

220V

IP40

Housing:


Cosmo housing is made up of pressure diecast aluminium with integral heat sink, bezel matt white finish for ceiling. Suitable for recessed mounting into a variety of false ceilings systems. Mounting through self mounting spring loaded clip attached to the fixture.

Optical:

Good colour rendering LED downlight, , choice of CCT 2700K-6500K at Ra>80, Diffused light is produced with Opal PMMA. LED is of SMD type , Low power in different wattages.

Electrical:

Recessed LED downlighter suitable for varied wattages with PF>.95 & driver efficiency of > 85%. Input power is 90-260VAC, 50Hz.



commercial area & office environment,
Residential space, Lobby

Product Name	Catalogue Reference No	Dimensions	Cut out size	Lamp wattage	Lumen output
COSMO	VAK- DL-COS-RD/SQ-R03	85x14	75mm	3W	300
	VAK-DL-COS-RD/SQ-R06	120x14	100mm	6W	600
	VAK-DL-COS-RD/SQ-R09	120x14	100mm	9W	900
	VAK-DL-COS-RD/SQ-R12	165x14	150MM	12W	1200
	VAK-DL-COS-RD/SQ-R18	225 x 14	200MM	18W	1800
	VAK-DL-COS-RD/SQ-R24	300 x14	275MM	24W	2400