

DIFFUSALUX

Make a strong statement of style
with a perfect harmony of acrylic and light

- Similar lighting performance as a traditional fluorescent but using significantly less energy.
- Long lamp life (up to 50,000 hours)
- Easy installation and maintenance
- Choice of color temperatures

INDOOR LIGHTING


SURFACE DOWNLIGHT



Housing: Diffusalux housing of Die Cast Aluminum. Proper integral heat sink, bezel matt white nish for ceiling.

Optical: Good colour rendering LED downlight, , choice of CCT 2700K-6500K at Ra>80, Difused light is produced with Opal PMMA. LED is of SMD type , Low power in different wattages.

Electrical: Diffusalux is suitable for Different wattage with PF>.95 & driver efficiency of > 85%. Input power is 90-240VAC, 50Hz.



commercial area & office environment,
Residential space, Lobby

Product Name	Catlogue Reference No	Dimensions (axb)	Lamp wattage	Lumen output
DIFFUSALUX	VAK- DL -DIF- SQ-S06	120x120	6W	600
	VAK- DL -DIF- SQ-S09	120x120	9W	900
	VAK- DL -DIF- SQ-S12	165x165	12W	1200
	VAK- DL -DIF- SQ-S15	165x165	15W	1500
	VAK- DL -DIF- SQ-S18	225x225	18W	2000
	VAK- DL -DIF- SQ-S24	300x300	24W	2400