


RADIANT

Robust bollard for modest lighting in residential and urban zones

- Simple design that appears unobtrusive in the landscape
- Head retained by recessed tamper-resistant bolt
- Low glare
- Balanced horizontal and vertical illumination due to lateral light diffusion
- Energy efficient LED system gives a fit and forget solution



Housing : Radiant body is made up with corrosion resistant Zinc plated ERW MS tubular sections. Base is made of galvanized die cast MS. Rubber gaskets are provided at appropriate location for dust and water protection

Optical: Diffuser is made of impact resistant PMMA specially designed for efficient light distribution. The exactitude optical system gives very low glare rating, while reducing light pollution

Electrical: Fitting is wired for 09W LED system

Finishing: Complete fitting is pure polyester based powder coated with high corrosion resistant and chemically chromotised protection. Also available with multiple coats of weather resistant polyurethane paint in various color.

OUTDOOR LIGHTING

BOLLARD

COLOR TEMPERATURE

3000K 4000K 6500K

220V IP65

140mm
850mm

Parks, Squares and pedestrian areas, Urban roads and streets, Bike paths, Precincts

| Product Name | Catlogue Reference No | Size (L)mm | LED Wattage | Ingress Protection |
|--------------|-----------------------|------------|-------------|--------------------|
| RADIANT | VAK-BL-RAD-S-09 | 850 | 09W | IP65 |