

SIENNA S

The fixture boast an innovative and unobtrusive low-profile housing shape, providing the perfect answer to constrained plenum space.

- Excellent light performance
- Encompasses high efficiency square thermoformed PMMA low glare diffuser.
- Fit & forget installation
- Long Lamp life(up to 50000 hrs) easy installation & maintainance
- Environmental friendly & maintainance free



INDOOR LIGHTING

SURFACE DOWNLIGHT



Housing :


Sienna Shousing of CRCA sheet steel white powder coated. Proper integral heat sink, bezel matt white finish for ceiling.

Optical:

Diffused light produced with UV stablised non yellowing PMMA, Good colour rendering LED downlight, , choiceof CCT 3000K-6500K at Ra>80,

Electrical:

Sienna S is available in varied wattage of 18/ 36/ 72W with PF>.95 & driver efficiency of > 85%.Input power is 90-240VAC, 50Hz.



commercial area & office environment,
Residential space, Lobby

Product Name	Catlogue Reference No	Dimensions (axb)	Lamp wattage	Lumen output
SIENNA S	VAK-DL-SIE-1X2-S18	300x600	18W	1800
	VAK-DL-SIE-2X2-S36	600x600	36W	3600
	VAK-DL-SIE-2x4-S72	600x1200	72W	7200