

BAND S

The Luminaire family enables various urban lighting tasks to be carried out in a uniform and strikingly attractive design

- Combines powerful and efficient LED optic
- Attack angle adjustable for 0° to 10°.
- Sleek aesthetic for modern applications, including high density housing, open spaces, Paths and city roads.
- Offer glare free light for a more pleasant urban environment.
- Wide range of combo from 50W to 150W.



Housing: Band housing made from aluminum profiles, aluminum alloy, MS section closed by toughed glass and durable silicon rubber gasket. Well designed housing resistant heat sensitive electrical component. The fitting is designed with very efficient thermal management system. Fitting is with 4 mtr rectangular pole in 50W and 6 mtr rectangular pole in 100W.]

Optical: UV resistant acrylic enclosure and high reflective, anodized aluminum street optic. With CRI>85 and high lumen efficacy giving the perfect illumination.

Electrical: fitting is wired with very high efficient LEDs. The wattage of Led can be customized. Standard wattage are from 50W to 100 W.

Finishing: Complete fitting is pure polyester based powder coated with high corrosion resistant and chemically chromotised protection.

COLOR TEMPERATURE

3000K 4000K 6500K

220V IP66

Urban Roads, Streets, Park, Residential Area, Parks, Car Parking, Bike Paths etc.

OUTDOOR LIGHTING

STREET LIGHT

| Product Name | Catlogue Reference No | Lumens | LED Wattage | Ingress Protection |
|--------------|-----------------------|--------|-------------|--------------------|
|--------------|-----------------------|--------|-------------|--------------------|

| | | | | |
|--------|----------------------------|-------|------|------|
| BAND S | VAK-ST-BAN-S-400-POLE-50 | 4000 | 50W | IP66 |
| | VAK-ST-BAN-S-600-POLE-75 | 6000 | 75W | IP66 |
| | VAK-ST-BAN-S-400-POLE-2x50 | 8000 | 100W | IP66 |
| | VAK-ST-BAN-S-600-POLE-2X75 | 12000 | 150W | IP66 |