

LUNIO S

A robust and durable spike of compact LED light for garden and park area

- Modular design offers a wide range of lighting possibilities
- Integral power supplies and Compactness
- Adjustable angle arrangement.
- Numerous and accurate light distributions



Housing: Lunio S spike light fitting made of decorative high corrosion resistant die cast aluminum, silicon rubber gasket, stainless steel fastener.

Optical: Diffuser made of toughened glass. Specially designed multifacet lens used for efficient light distribution. Fitting has Symmetrical light distribution.

Electrical: Fitting is wired with energy efficient power led having long service life, MCPCB and wide voltage range constant current driver.

Finishing: Complete fitting is pure polyester based powder coated with high corrosion resistance and chemical chromatised protection.

COLOR TEMPERATURE

3000K 4000K 6500K

220V IP66

OUTDOOR LIGHTING
SPOT LIGHT

N M W

Shurb, Tree, Landscape, Parks, Sculptures,
Monuments, Facade etc.

Product Name	Catlogue Reference No	Lumens	LED Wattage	Ingress Protection
LUNIO S	VAK-SL-LUN-SPIKE-G10	800	10	IP66
	VAK-SL-LUN-SPIKE-G20	1600	20	IP66
	VAK-SL-LUN-SPIKE-G30	2400	30	IP66