

PULSE

It is a matter of always being able to create the right setting and brightness when and where you want


- Similar lighting performance as a traditional fluorescent but using significantly less energy with LED engine.
- Express safety, strength and harmony in urban lighting application
- Elegant design and shape for landscape
- Optic and heat dissipater protected to IP 65
- Choice of color temperatures
- Quality by Design to minimize your Total Cost of Ownership

OUTDOOR LIGHTING

BOLLARD



COLOR TEMPERATURE



3000K




Housing: Pulse body is made up with corrosion resistant pressure die cast aluminium. Base is made of die cast aluminium. Rubber gaskets are provided at appropriate location for dust and water protection

Optical: Diffuser is made of impact resistant PMMA/ PC specially designed for efficient light distribution. Color of the light is 3000K. The exactitude optical system gives very low glare rating, while reducing light pollution.

Electrical: Fitting is wired for LEDs engine.

Finishing: Complete fitting is pure polyester based powder coated with high corrosion resistant and chemically chromotised protection. Also available with multiple coats of weather resistant polyurethane paint in various colors.



400MM

Parks, Squares and pedestrian areas, Urban roads and streets, Bike paths, Precincts

Product Name	Catalogue Reference No	Size (L)mm	LED Wattage	Ingress Protection
PULSE	VAK-BL-PUS-S-07	400	7W	IP65