

XENTRICS

Feature rich installation, integration with ceilings and presentation of artworks, texture and architectural

- Mainbody with radiant surface made of Diecast aluminium.
- High definition optics made of metallised thermos plastic material.
- Innovative black antiglare screen that defines emission with luminance control.
- Available tunable white versions.
- The special configuration of optical system delivers a precise circular distribution without punctiform effect.
- High visual comfort.



INDOOR LIGHTING

RECESS DOWNLIGHT

COLOR TEMPERATURE

3000K 4000K 6500K

220V IP40

Housing: Xentrics housing is made of pressure diecast aluminium with integral heat sink, bezel matt finish for Ceiling. Suitable for recessed mounted on a variety of fall ceilings systems. Mounting through self mounting spring loaded clip attached to the fixture.

Optical: High efficient LED Module in COB Technology with Constant Current driver. Fitting is with good colour rendering Ra>80.

Electrical: Recessed LED downlighter suitable for 2W to 10W with PF>.95 & driver efficiency of >85%. Input power is 90-240VAC, 50Hz.

Possibilities of various ceiling patterns



commercial area & office environment, Residential space, Lobby

Product Name	Catalogue Reference No	Dimensions	Cut out size	Lamp wattage	Lumen output
XENTRICS	VAK-DL-XEN-R-2	44.5X44.5	38x38	2W	200
	VAK-DL-XEN-R-2x2	44.5x73	38X65	2x2W	400
	VAK-DL-XEN-R-5x2	44.5x148	38X135	2x5W	1000
	VAK-DL-XEN-R-10x2	44.5x281	38X268	2x10W	2000